

Canon

imageRUNNER®
5020 / 6020 SERIES



DEPARTMENTAL
SYSTEMS



meap
POWERED BY


A UNIQUE PLATFORM DESIGNED SOLELY FOR YOUR SPECIFIC BUSINESS APPLICATIONS.

Canon's imageRUNNER® 5020/6020 Series is a highly advanced digital imaging solution that tightly integrates with every aspect of your workflow. Incorporating Canon's MEAP™ (Multifunctional Embedded Application Platform) architecture, the imageRUNNER 5020/6020 Series gives your business greater control over costs and productivity by embedding diverse and customizable applications for a wide range of business workflow requirements.


The imageRUNNER 5020 and imageRUNNER 5020i each deliver output at a fast 50 pages per minute, while the imageRUNNER 6020 and imageRUNNER 6020i take your output productivity to speeds of 60 pages per minute. No matter which model you choose, you will benefit from Canon's industry-renowned image quality for the most faithful reproduction of text and images.

imageRUNNER 5020/6020 Series Specifications

Type:	Digital, Multifunction Imaging System	Paper Weights:	17 lb. to 24 lb. Bond (550-sheet Cassettes) 17 lb. to 110 lb. Index (Manual Bypass, 1,500-sheet Drawers and 3,500-sheet Optional Paper Deck-G1)	Lower Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (All Sizes)
Imaging System:	Laser Dry Electrostatic Transfer	Dimensions (H x W x D):	44-3/4" x 25-3/8" x 29-1/4" (1136mm x 643mm x 743mm)	Staple Position:	1-Top Corner 2-Side Margin
Developing System:	Dry Monocomponent Toner Projection	Installation Space (W x D):	52-3/8" x 29-1/4" (with copy tray)	Max. Stapling Capacity:	50 Sheets (Letter/Statement) 30 Sheets (Letter-R/Legal/Ledger)
Image Server Memory:	Standard 256MB RAM + 10GB HDD (Max. Capacity: Approximately 3,700 Originals)	Weight:	462 lb. (210kg)	Power Source:	Directly from Main Unit
First-copy Time:	3.8 Seconds from Platen Glass 5.1 Seconds from ADF	Power Requirements:	115V/60Hz, 15A	Dimensions (H x W x D):	41-3/8" x 26-3/8" x 24-1/4" (1052mm x 669mm x 614mm)
Warm-up Time:	5 Minutes or Less (5020/5020i) 6 Minutes or Less (6020/6020i)	Power Consumption:	1.5KW	Weight:	Approximately 70.5 lb. (32kg)
Acceptable Originals:	Sheets, Books, 3-dimensional Items (Up to 4.4 lb.)	Plug:	NEMA 5-20P	Type of Staple:	Staple-E1 (5,000 x 3)
Max. Original Size:	11" x 17" (Ledger)	Drum:	Amorphous Silicon – Estimated Yield: 3,000,000 Impressions	Attachable Accessories:	Puncher Unit-B1 (2-/3-hole punch)
Max. Copy Size:	11" x 17" (Ledger)	Maximum Duty Cycle:	5020: 200,000 Impressions/Month 6020: 230,000 Impressions/Month	Saddle Finisher-F2 (Optional)	
Min. Copy Size:	4-1/8" x 5-7/8"	Toner:	Magnetic Negative Toner – Estimated Yield: 33,000 Images (at 6% Coverage)	Acceptable Paper Weight:	17 lb. Bond to 110 lb. Index
Max. Mail Boxes Supported:	100	Sending Functions (5020i/6020i)		Number of Trays:	2 Trays
Max. Copy Reservation:	5 Jobs	Sending Methods:	E-mail, I-fax, Database (Salutation), File Server (IPX, FTP, SMB)	Tray Capacity	
Copy/Scanning Resolution:	600 dpi x 600 dpi	Address Book Capacity:	Maximum 1,800	Top Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (w/Staple) (All sizes)
Printing Resolution:	600 dpi x 600 dpi 2400 dpi x 600 dpi Interpolated	File Format:	Single-page TIFF, Single-page PDF, Multipage TIFF, PDF	Lower Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (w/Staple) (All Sizes)
Half-tone:	256 gradations of gray	Sending Sizes:	Statement to Ledger	Staple Position:	1-Top Corner 2-Side Margin
Automatic Exposure:	AE or Manual (Text, Photo, or Text and Photo)	Scanline Density:	200 x 200 dpi, 300 x 300 dpi 200 x 400 dpi, 600 x 600 dpi	Max. Stapling Capacity:	50 Sheets (Letter/Statement) 30 Sheets (Letter-R/Legal/Ledger)
Copy Speed:	5020: 50 ppm (Letter) 36 ppm (Legal) 30 ppm (Ledger) 39 ppm (Letter-R) 50 ppm (Statement-R) 6020: 60 ppm (Letter) 36 ppm (Legal) 30 ppm (Ledger) 42 ppm (Letter-R) 60 ppm (Statement-R)	Accessories		Saddle-stitch Tray	
Duplexing:	Standard Automatic Trayless Duplexing	Automatic Document Feeder (Standard)		Tray Capacity:	300 Sheets
Magnification:	25% - 400% (in 1% Increments) from glass 25% - 200% (in 1% Increments) from feeder	Acceptable Originals:	Statement to Ledger	Paper Weight:	17 lb. to 22 lb. Bond; Cover sheet is up to 110 lb. Index
Preset Reduction/Enlargement:	25%, 50%, 64%, 73%, 78%, 121%, 129%, 200%, 400%	Capacity:	100 Sheets (Letter/20 lb.)	Total Sides Imaged:	60 Total Sides (15 Sheets)
Paper Supply Standard:	Dual Front-loading Trays (1,500 Sheets Each) Dual Front-loading Cassettes (550 Sheets Each) 50-sheet Stack Bypass 3,500-sheet Paper Deck (Total: 7,650 Sheets)	Max. Paper Weight:	13 lb. to 32 lb. Bond (Letter)	Total Sets:	25 Total Sets (1 to 5 Sheets) 15 Total Sets (6 to 10 Sheets) 10 Total Sets (11 to 15 Sheet)
Optional:		Original Replacement Speed:	Standard 55 ipm	Folding:	V-folding (Standard)
Multiple Copies:	1 to 9,999	Original Feeding Method:	From first page (top of original)	Paper Size Supported:	Letter-R, Ledger
		Power Source:	Directly from Main Unit	Power Source:	Directly from Main Unit
		Weight:	Approximately 30.8 lb. (14kg)	Dimensions (H x W x D):	41-3/8" x 26-3/8" x 24-1/4" (1052mm x 669mm x 614mm)
		Finisher-F1 (Optional)		Weight:	Approximately 114 lb. (52kg)
		Acceptable Paper Weight:	17 lb. Bond to 110 lb. Index	Type of Staple:	Staple-E1 (5,000 x 3) Staple Cartridge-D2 (2,000 x 3 Cartridges) for Saddle-stitch Unit
		Paper Size:	Statement to Ledger	Attachable Accessories:	Puncher Unit-B1 (2-/3-hole punch)
		Number of Trays:	2 Trays		
		Tray Capacity			
		Top Tray:	1,000 Sheets (Letter) 500 Sheets (Ledger) Offset Stacking: Max. 30 Sets (All Sizes)		



Saddle Finisher-F2



Finisher-F1

Puncher
Unit-B1 **

Main Unit



Paper Deck-G1

imagePASS-M2
Print Controller **

imageRUNNER 5020/6020 Series Specifications (continued)

Puncher Unit-B1 (Optional)**

Max. Paper Weight:	Up to 110 lb. Index
Paper Size:	Letter, Legal, Ledger
Punch Method:	Sequential processing system (one sheet at a time)
Punch Types:	2-hole/3-hole (Auto Change) 3-hole (Letter/Ledger) 2-hole (Legal/Letter-R)
Punch Dust Stock:	Approximately 3,000 Sheets
Punch Dust Access:	Front
Power Source:	120W Directly from Main Unit
Dimensions (H x W x D):	34-7/8" x 3" x 24-1/4" (886mm x 75.5mm x 614.4mm)
Weight:	Approximately 11.9 lb. (5.4kg)

Paper Deck-G1 (Optional)

Number of Drawers:	1
Paper Capacity:	3,500 Sheets (20 lb. Bond)
Paper Size:	Letter
Paper Weight:	17 lb. Bond to 110 lb. Index
Power Source:	Directly from Main Unit
Dimensions (H x W x D):	22-5/8" x 12-3/4" x 23" (574mm x 323mm x 583mm)
Weight:	Approximately 101 lb. (46kg)

**Network Multi-PDL Printer Kit-D1
(Standard with 5020i/6020i)**

Processor:	Canon Custom Processor— Shared
RAM:	256MB (Std./Max.)—Shared
Hard Disk:	10GB
PDL Support:	PCL 5e, PCL 6, PostScript® 3 Emulation
Interface Connections:	RJ-45 (10/100Base-T) IEEE 1284 (Compatibility: Nibble, Byte and ECP Mode) Token Ring (Optional Card)
Internal Fonts:	PS: 136 Fonts (117 Adobe Type and 19 TrueType)
Protocol Stacks:	PCL 5e/6: Roman 80, Bar code 32 NetWare®: 802.2, 802.3, Ethernet II, 802.2 SNAP TCP/IP: Ethernet II AppleTalk®: Phase II
Network OS:	Novell® NetWare® v.3.2, 4.1, 4.1.1, 4.2, 5, 5.1, 6 Windows® 95/98/Me/NT 4.0/ 2000/XP Solaris™ 1.x, 2.5 or later Apple® System 7.5 or higher
Print Service:	NetWare: NDS Pserver, Pserver, Nprinter, Rprinter TCP/IP: LPD (Line Printer Daemon), IPP (Windows 9.X, 2000 only), RAW (Windows 2000 only), SMB AppleTalk: PAP

Utilities and Software:
Additional Functions:

NetSpot,® NetSpot Console
Remote UI™
Network ScanGear
JBIG Viewer
NetSpot Resource Downloader
EMS Open View
EMS NetView
EMS Unicenter® TNG

imagePASS-M2 (Optional)**

Type:	Intel® Pentium® III External Stand-alone Controller
Processor:	1GHz Processor
RAM:	128MB Standard
Hard Disk:	20GB
PDL Support:	Adobe PostScript® 3,™ PCL 5e, PCL 6
Interface Standard:	10/100Base-T (RJ-45), Parallel Port (Type B Connector)
Optional: Internal Fonts:	Token Ring PS: 136 Fonts (117 Adobe Type and 19 TrueType®)
Protocol Stacks:	PCL 5e/6: Roman 80 Ethernet IPX/SPX: 802.2, 802.3, Ethernet II, Ethernet SNAP, Token Ring, Token Ring SNAP TCP/IP: Ethernet II, Token Ring SNAP AppleTalk: Ethernet SNAP
Network OS:	Novell® NetWare® v.4.1, 4.2, 5, 5.1 (IPX/SPX) Windows® 95/98/Me/NT 4.0/ 2000/XP (TCP/IP) Solaris™ 2.5.1 or later (TCP/IP) Apple® System 8.6, 9, 9.1 (DDP) 15.5" x 6.375" x 15.75" (393mm x 162mm x 400mm)
Dimensions (H x W x D):	21 lb.
Weight:	100 to 240VAC, 50/60Hz, 1A 60.5W
Power Requirements:	Power Consumption:
Utilities and Software:	NetSpot,® NetSpot Console Remote UI,™ Network ScanGear, JBIG Viewer, NetSpot Resource, Downloader, EMS Open View, EMS NetView, EMS Unicenter® TNG WebTools,™ Command WorkStation,™ WebStatus,™ Fiery® Tools:
Additional Functions:	Fiery Downloader,™ Web Setup, Fiery Spooler,™ WebSpooler,™ Fiery Link,™ WebLink, Freeform + Job Log, PowerForm, DocBuilder™

Other Optional Accessories and Utilities

Copy Tray-C3
Control Card IV
Control Card Printer-A1
Card Sets
Accessibility Handle-A1
Resolution Switching Board-B1
Token Ring-A2 Set
USB Application Interface Board-A1
I-O 5435dp
imageRUNNER Security Kit-A1P
imageWARE™ Suite
NetSpot Suite
eCopy Suite


* Check with your local Canon-authorized Dealer for availability.

**Puncher Unit-B1 can only be installed with the Finisher-F1 and Saddle Finisher-F2.

^ For the imageRUNNER 5020/6020 models only; not available for the i models.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR certification mark are registered U.S. marks. Microsoft, Windows, and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. Adobe and PostScript are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. Apple, AppleTalk and TrueType are registered trademarks of Apple Computer, Inc. Intel and Pentium are registered trademarks of Intel Corporation. Novell and NetWare are registered trademarks of Novell, Inc. in the United States and other countries. IPX/SPX is a trademark of Novell, Inc. NetView is a registered trademark of IBM in the United States. Solaris is a trademark of Sun Microsystems, Inc. in the United States and other countries. Unicenter is a registered trademark of Computer Associates International, Inc. Fiery is a registered trademark of Electronics for Imaging, Inc. in the U.S. Patent and Trademark Office and certain other foreign jurisdictions. EFI, Command WorkStation, Fiery Downloader, Fiery Link, Fiery Spooler, WebSpooler, WebTools, WebStatus, and DocBuilder are trademarks of Electronics for Imaging, Inc. Canon and NetSpot are registered trademarks, and MEAP, Universal Send, Canon Know How, and the GENUINE logo are trademarks of Canon, Inc. IMAGERUNNER is a registered trademark of Canon Inc. in the U.S. and Canada. IMAGEWARE and Remote UI are trademarks, and IMAGEANYWARE is a service mark of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

0603-iR5020/6020-PDF

 PRINTED ON RECYCLED
PAPER IN THE U.S.A.



Canon KNOW HOW™

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042